

## PK/PUK Series



PK100300



PK2090IS2

ISO-9002 Class-A  

MODEL	PK2090IS2	PK30120	PK50160	PK75250	PK100300	PK150300	PK200300	PK300500
HP	2	3	5	7.5	10	15	20	30
KW	1.50	2.20	3.75	5.60	7.50	11.2	15.0	22.0
DISPLACEMENT (L / MIN / CFM)	300/10.6	465/16.4	751/26.5	1118/39.5	1538/54.3	2198/77.6	3000/106	3805/134
R.P.M	983	771	830	890	816	648	750	950
No. of CYL	2	2	3	2	3	3	6	6
MAX PRESSURE (KG / CM <sup>2</sup> / PSI)	10/142	10/142	10/142	10/142	10/142	10/142	10/142	10/142
WORKING PRESSURE (KG / CM <sup>2</sup> / PSI)	8/115	8/115	8/115	8/115	8/115	8/115	8/115	8/115
TANK CAPACITY	88/23	120/32	160/42	250/66	300/79	300/79	300/79	500/132
N.W (KG / LBS.)	97/213	144/316	199/437	301/662	362/796	534/1174	425/995	651/1432
DIMENSION (cm)	117x49x85	132x53x96	155x58x106	161x70x115	191x76x121	191x76x142	191x76x142	201x80x145